

□製品規格表-1(L-screen・UX-screen・EX-screen 115~155cm巾)

商品名	品番		メッシュ数		線径 μm	厚さ 115-155cm		オープニング μm	オープニングエリア %	透過体積 cm <sup>3</sup> /m <sup>2</sup>	製品巾(生産対応)		
	新品名	旧品名	/cm	/inch		μm	μm				115cm	136cm	155cm
L-screen	200-027/508TW	508-27 2/2	200	508	27	52	23	21	11	◎	○	○	
	180-027/460PW	460-27	180	460	27	41	28	26	11	◎	◎	◎	
	180-030/460TW	460-30 2/2	180	460	30	55	25	21	11				
	165-027/420PW	420-27	165	420	27	40	33	30	12	◎	◎	◎	
	150-027/380PW	380-27	150	380	27	40	40	36	14				
	150-030/380PW	380-30	150	380	30	45	37	30	14	◎	◎	◎	
	140-027/355PW	355-27	140	355	27	40	45	39	16				
	140-030/355PW	355-30	140	355	30	45	42	34	15	◎	◎	◎	
	130-027/330PW	330-27	131	334	27	40	49	42	17			○	
	130-030/330PW	330-30	131	334	30	45	46	37	16	◎		◎	
	124-027/315PW	315-27	124	315	27	40	54	44	18	○	○	◎	
	124-030/315PW	315-30	124	315	30	45	51	40	18	○	○	◎	
	120-030/305PW	305-30	120	305	30	46	53	41	19	◎	◎	◎	
	120-035/305PW	305-35	120	305	35	53	48	34	18	◎	◎	◎	
	110-035/280PW	280-35	110	280	35	53	56	38	20	◎	◎	◎	
	100-035/255PW	255-35	100	255	35	53	65	42	22	◎	◎	◎	
UX-screen	165-033/420TW	420T2/2	165	420	33	60	27	21	12	◎	○	◎	
	150-033/380PW	380M	150	380	33	48	34	26	12	◎	◎	◎	
	150-035/380TW	380T2/2	150	380	35	64	32	23	15	◎			
	140-035/355PW	355T	140	355	35	53	37	26	14	◎	◎	◎	
	140-035/355TW	355T2/1	140	355	35	61	37	26	16	◎			
	130-035/330PW	330T	130	330	35	53	42	30	16	◎			
	120-033/305PW	305M	120	305	33	50	50	36	18	◎	◎	◎	
	120-035/305PW	305T	120	305	35	53	48	34	18	◎	◎	◎	
	118-040/300PW	305HD	118	300	40	62	45	28	17	○	○	○	
	110-035/280PW	280T	110	280	35	53	56	38	20	◎	◎	◎	
	106-040/270PW	270HD	106	270	40	60	54	33	20	◎	◎	◎	
	100-035/255PW	255S	100	255	35	53	65	42	22	◎	◎	◎	
	100-040/255PW	255T	100	255	40	60	60	36	21	◎	◎	◎	
	90-040/230PW	230S	90	230	40	60	70	41	24	◎	○	◎	
	90-045/230PW	230T	90	230	45	68	65	35	24	◎	◎	◎	
	EX-screen	89-048/225PW	225H	88	225	48	75	65	33	25	◎	○	○
	EX-screen	89-055/225TW	225HD2/1	88	225	55	91	58	26	24	◎	○	○
	UX-screen	79-045/200PW	200S	79	200	45	68	82	42	28	◎	◎	◎
	EX-screen	79-048/200PW	200M	79	200	48	75	79	39	29	◎	◎	◎
	EX-screen	79-055/200PW	200T	79	200	55	88	72	32	28	◎	◎	◎
UX-screen	71-045/180PW	180S	71	180	45	70	96	46	32	◎			
EX-screen	71-048/180PW	180M	71	180	48	76	93	44	33	◎	◎	◎	
	71-055/180PW	180T	71	180	55	88	86	37	33	◎	○	◎	
	63-048/160PW	160M	63	160	48	80	111	49	39				
UX-screen	63-063/160PW	160H	63	160	63	105	96	36	38				
UX-screen	59-045/150PW	150S	59	150	45	72	124	54	39	◎			
EX-screen	59-048/150PW	150M	59	150	48	76	121	51	39	◎		◎	
	59-055/150PW	150T	59	150	55	88	114	46	40	◎	◎	◎	
	59-063/150PW	150H	59	150	63	105	106	39	41				
UX-screen	55-063/140PW	140H	55	140	63	105	118	43	45				
EX-screen	53-045/135PW	135S	53	135	45	73	143	58	42				
	53-048/135PW	135M	53	135	48	79	140	55	44				
	53-055/135PW	135T	53	135	55	95	133	50	48	◎		◎	
UX-screen	49-071/125PW	125H	49	125	71	116	132	42	49				
UX-screen	47-045/120PW	120S	47	120	45	73	167	62	45	◎			
EX-screen	47-048/120PW	120MS	47	120	48	80	164	60	48				
	47-055/120PW	120M	47	120	55	95	157	55	52	◎		◎	
	47-063/120PW	120T	47	120	63	105	149	49	52	○	○	○	
	43-080/110PW	110HD	43	110	80	132	151	43	56	○	○	○	
	39-055/100PW	100S	39	100	55	95	199	61	58	◎		○	
	39-071/100PW	100T	39	100	71	122	183	52	63	◎	◎	◎	
	39-080/100PW	100H	39	100	80	134	174	47	63				
	35-071/90PW	90S	35	90	71	125	211	56	70	◎			
	35-080/90PW	90T	35	90	80	137	202	51	70	◎			
	31-071/80PW	80S	31	80	71	125	247	60	75	◎		◎	
	31-100/80PW	80T	31	80	100	170	218	47	80	◎		◎	
	27-071/70PW	70S	27	70	71	125	292	65	81	◎		◎	
27-125/70PW	70HD	27	70	125	240	238	43	103					
24-125/60PW	60T	24	60	125	230	298	50	114					
24-150/60PW	60HD	24	60	150	260	273	42	108					

■オープニング・オープニングエリア・透過体積はメッシュ数・線径に基づく計算値となります。

■製品名の記号について

PW … 平織り TW … 綾織

■生産対応

◎: 通常生産品

○: 準通常生産品(実績に基づく継続生産品)

×: 対応不可品

空欄: 受注生産品 ※生産ロット・納期は別途お問合せください。

※受注生産品でも在庫ある場合がございますので別途お問合せください。

※上記生産状況区分は、弊社在庫保有・供給体制を保证するものではありません。