

タイプ	品番		メッシュ数		線径	推奨テンション値		
						標準テンション mm(N/cm)	高テンション mm(N/cm)	エキスパート テンション mm(N/cm)
	新品名	旧品名	/cm	/inch	μm	破断テンション × 60%	破断テンション × 70%	破断テンション × 90%
L-	180-027/460PW	460-27	180	460	27	1.58(18)	1.35(21)	1.06(27)
	165-027/420PW	420-27	165	420	27	1.58(18)	1.35(21)	1.06(27)
	150-027/380PW	380-27	150	380	27	1.58(18)	1.35(21)	1.06(27)
	150-030/380PW	380-30	150	380	30	1.29(22)	1.09(26)	0.87(33)
	140-027/355PW	355-27	140	355	27	1.80(16)	1.58(18)	1.19(24)
	130-027/330PW	330-27	134	334	27	1.93(15)	1.68(17)	1.29(22)
	130-030/330PW	330-30	134	334	30	1.42(20)	1.24(23)	0.96(30)
	124-027/315PW	315-27	124	315	27	1.93(15)	1.58(18)	1.24(23)
	124-030/315PW	315-30	124	315	30	1.48(19)	1.24(23)	0.98(29)
EX	180-027/460PW	460S	180	460	27	1.80(16)	1.48(19)	1.19(24)
	180-030/460TW	460T	180	460	30	1.06(27)	0.89(32)	0.72(41)
	165-027/420PW	420S	165	420	27	1.80(16)	1.48(19)	1.19(24)
	165-030/420PW	420M	165	420	30	1.19(24)	1.02(28)	0.79(36)
	165-033/420TW	420T	165	420	33	1.14(25)	0.98(29)	0.76(38)
	150-030/380PW	380S	150	380	30	1.35(21)	1.14(25)	0.89(32)
EX/UX	150-033/380PW	380M	150	380	33	1.24/1.14 (23/25)	1.09/0.98 (26/29)	0.84/0.76 (34/38)
EX	150-035/380TW	380T	150	380	35	1.06(27)	0.92(31)	0.73(40)
	140-030/355PW	355S	140	355	30	1.35(21)	1.14(25)	0.89(32)
EX/UX	140-035/355PW	355T	140	355	35	1.09/0.98 (26/29)	0.96/0.78 (30/37)	0.74/0.73 (39/40)
EX	130-030/330PW	330S	130	330	30	1.58(18)	1.35(21)	1.06(27)
	130-033/330PW	330M	130	330	33	1.35(21)	1.19(24)	0.92(31)
	130-035/330PW	330T	130	330	35	1.06(27)	0.89(32)	0.72(41)
	120-030/305PW	305S	120	305	30	1.80(16)	1.48(19)	1.19(24)
EX/UX	120-033/305PW	305M	120	305	33	1.42/1.35 (20/21)	1.24/1.14 (23/25)	0.96/0.89 (30/32)
	120-035/305PW	305T	120	305	35	1.24/1.14 (23/25)	1.06/0.96 (27/30)	0.82/0.76 (35/38)
EX	120-040/305PW	305HD	118	300	40	1.09(26)	0.96(30)	0.76(38)
EX/UX	110-035/280PW	280T	110	280	35	1.24/1.14 (23/25)	1.06/0.98 (27/29)	0.82/0.78 (35/37)
	106-040/270PW	270HD	106	270	40	1.14/1.02 (25/28)	0.96/0.87 (30/33)	0.76/0.69 (38/42)
UX	100-035/255PW	255S	100	255	35	1.29(22)	0.79(36)	0.87(33)
EX/UX	100-040/255PW	255T	100	255	40	1.24/1.06 (23/27)	1.06/0.92 (27/31)	0.82/0.73 (35/40)
	90-040/230PW	230S	90	230	40	1.29/1.09 (22/26)	1.09/0.96 (26/30)	0.87/0.74 (33/39)

EX	90- 045/230PW	230T	90	230	45	1.06(27)	0.89(32)	0.72(41)
	79- 045/200PW	200S	79	200	45	1.09(26)	0.96(30)	0.74(39)
	79- 048/200PW	200M	79	200	48	1.09(26)	0.96(30)	0.74(39)
	79- 055/200PW	200T	79	200	55	1.06(27)	0.89(32)	0.72(41)
	71- 045/180PW	180S	71	180	45	1.29(22)	1.14(25)	0.87(33)
	71- 055/180PW	180T	71	180	55	1.06(27)	0.92(31)	0.73(40)
	63- 063/160PW	160H	63	160	63	1.06(27)	0.92(31)	0.73(40)
	59- 048/150PW	150M	59	150	48	1.35(21)	1.19(24)	0.92(31)
	59- 055/150PW	150T	59	150	55	1.29(22)	1.09(26)	0.87(33)
	59- 063/150PW	150H	59	150	63	1.06(27)	0.92(31)	0.73(40)
	55- 063/140PW	140H	55	140	63	1.06(27)	0.92(31)	0.73(40)
	53- 048/135PW	135M	53	135	48	1.58(18)	1.35(21)	1.06(27)
	53- 055/135PW	135T	53	135	55	1.35(21)	1.19(24)	0.92(31)
	49- 071/125PW	125H	49	125	71	1.06(27)	0.92(31)	0.73(40)
	47- 048/120PW	120MS	47	120	48	1.58(18)	1.35(21)	1.06(27)
	47- 055/120PW	120M	47	120	55	1.58(18)	1.35(21)	1.09(26)
	47- 063/120PW	120T	47	120	63	1.09(26)	0.92(31)	0.73(40)
	43- 080/110PW	110HD	43	110	80	1.06(27)	0.92(31)	0.73(40)
	39- 055/100PW	100S	39	100	55	1.68(17)	1.42(20)	1.09(26)
	39- 071/100PW	100T	39	100	71	1.06(27)	0.89(32)	0.72(41)
	35- 071/90PW	90S	35	90	71	1.09(26)	0.96(30)	0.74(39)
	35- 080/90PW	90T	35	90	80	1.06(27)	0.92(31)	0.73(40)
	31- 071/80PW	80S	31	80	71	1.09(26)	0.96(30)	0.74(39)
	31- 100/80PW	80T	31	80	100	1.06(27)	0.89(32)	0.72(41)
	27- 071/70PW	70S	27	70	71	1.29(22)	1.14(25)	0.87(33)
	24- 125/60PW	60T	24	60	125	1.06(27)	0.89(32)	0.72(41)